Arcus



Cesta 24. junija 23, 1231 Ljubljana, Slovenija, tel: +386 1 5890513, fax +386 1 5890515, E-mail: vega@vega.si, www.vega.si

ARCUS

The new, low cost, attractive OHP



Arcus folded





Front panel

Cable compartment



Rotating head (360°)

The OHP can still be attractive. In spite of many modern presentation devices on the market it is a still very powerful tool. The Arcus OHP range continues the highly successful VEGA OHP tradition. Arcus is designed for those demanding the highest quality presentation aid, but have a limited budget. Different models (250W and 400W) will satisfy diverse educational and business applications. Arcus features foldable arm, special silent cooling system, cable compartment and carefully chosen optical elements. A specially designed rotating head (360°) enables all-round projection. All models are equipped with two lamps with a fast lamp-changer. The integrated colour correction system (fringing) enables a better range of picture sizes and distances.

Arcus is equipped with unique Vega optical elements, designed and manufactured by Vega, which is one of the key strengths of Vega's products. Many years of experience has led to the achievement of perfect quality as regards optics - this being confirmed by references from our partners and customers throughout the world.

Model	Arcus 250 XLS	Arcus 250 YLS	Arcus 250 GLS	Arcus 400 YLS	Arcus 400 GLS
Туре	Table top				
Lamp (W/V)	250/24	250/24	250/24	400/36	400/36
Lamp type	EHJ	EHJ	EHJ	EVD	EVD
Lamp changer	Yes	Yes	Yes	Yes	Yes
Power supply	Transformer	Transformer	Transformer	Transformer	Transformer
Lamp saver/ Eco switch	Yes	Yes	Yes	Yes	Yes
Blown lamp indicator	No	No	No	No	No
Projection Lens (elements)	1-fixed	3-fixed	3-fixed	3-fixed	3-fixed
Focal length f=mm	295	315	315	315	315
Rotated head	Yes	Yes	Yes	Yes	Yes
Picture Width (cm) min/max	100/400	90/400	90/400	90/400	90/400
Projection Distance (cm) min/max	120/450	120/450	120/450	120/450	120/450
Condenser	No	No	Yes	No	Yes
Working surface (mm)	285x285	285x285	285x285	285x285	285x285
Foldable post	Yes	Yes	Yes	Yes	Yes
Fringing	Yes	Yes	Yes	Yes	Yes
Thermo cut-off	Yes	Yes	Yes	Yes	Yes
Light output (Lumens)	2100	2300	2600	4500	5200
Net Dimensions Unfolded (mm) LxWxH	365x385x600	365x385x600	365x385x600	365x385x600	365x385x600
Net Dimensions Folded (mm) LxWxH	550x385x290	550x385x290	550x385x290	550x385x290	550x385x290
Weight (kg) Net/Gross (packed)	10,8/12	11/12,2	11,1/12,3	11,5/12,7	11,6/12,8